

# Qoltec DisplayPort v2.1 male cable | DisplayPort v2.1 male | 8K | 54G | 5m

**Product code: 52737**

The DisplayPort 2.1 DP80 cable with UHBR13.5 support offers a bandwidth of up to 54 Gb/s, enabling the transmission of high-resolution video, including 8K, while maintaining a stable signal thanks to its shielded design.

## IT'S TIME FOR BETTER PICTURE AND SOUND QUALITY




Ideal for Multimedia, Work and Gaming – 8K, DP80 and UHBR13.5

**Discover a new level of picture and sound quality with the DisplayPort 2.1 DP80 cable** . With support for **UHBR13.5 technology and a bandwidth of up to 54 Gb/s** , the cable enables stable high-resolution signal transmission, including up to 8K. It is the perfect solution for work, multimedia and gaming, where smooth visuals, detail and a reliable connection are essential. **The shielded design helps to minimise interference**, ensuring stable operation and high-quality signal transmission.

## YOUR KEY TO PERFECT PICTURE AND SOUND




8K cable, compatible with TVs, laptops and home cinema systems
This is a practical choice for users who expect high-quality images, smooth performance and a reliable connection on a daily basis. The cable is ideal for both home multimedia set-ups and more demanding computer configurations.
- **Supports resolutions up to 8K –** detailed images and high display quality,
- **Bandwidth up to 54 Gb/s, –** fast and stable signal transmission,
- **DP80 / UHBR13.5 standard –** a modern solution for demanding users,
- **Video and audio transmission via a single cable –** a convenient connection without additional audio cables,
- **Wide compatibility –** can be connected to a computer, laptop, monitor, projector, docking station or graphics card with a DisplayPort,
- **Shielded design –** reduces interference and ensures stable operation of devices.

## DISPLAYPORT 2.1 – THE PERFECT CHOICE FOR WORK AND ENTERTAINMENT



Version 2.1 – Bandwidth up to 54 Gb/s and 8K support

The DisplayPort 2.1 DP80 cable is a state-of-the-art solution for users who expect high-quality images, stable transmission and smooth performance. **With support for UHBR13.5 and a bandwidth of up to 54 Gb/s, it enables the transmission of high-resolution signals, including up to 8K** , making it ideal for work, watching multimedia and gaming. Compared to earlier versions of the standard, DisplayPort 2.1 DP80 offers higher bandwidth and better support for demanding display set-ups.

## FLEXIBLE DESIGN, RELIABLE SIGNAL




Shielding, CCS and 30AWG – stable transmission and convenient use

The cable's shielded design helps to minimise the impact of electromagnetic interference, ensuring stable transmission of picture and sound even during intensive use. **The cable, manufactured using CCS technology (copper-clad steel), combines adequate mechanical strength with good signal conductivity, whilst the 30 AWG gauge ensures the cable remains flexible and convenient for everyday use.**

## TRUST BACKED BY A GUARANTEE

This product comes with a 2-year warranty

Do you care about the high quality of the product you're buying? **Our solutions are designed to meet your expectations.** Each of the DisplayPort cables we offer is covered by a 24-month warranty valid from the date of purchase.

## TECHNICAL DATA

| | |
|---|---|
| Producer | Qoltec |
| Type | DisplayPort male / DisplayPort male |
| Standard | DP v2.1 |
| Class | DP80 / UHBR13.5 |
| Data transfer | 54 Gb/s |
| AWG cross section | 30AWG |
| Conductor construction | CCS |
| Resolution | 8K |
| Application | laptop, PC |
| Additional information | Ekranowany<br>Obsługiwana rozdzielczość i częstotliwość odświeżania zależą od parametrów urządzenia źródłowego, monitora oraz zastosowanych ustawień |
| OTHER PARAMETERS | |
| Colour | Black |
| Insulating material | PVC |
| Working temperature | -20 C ~ +60 |
| Cable length | 5 m |
| Package | Blister |
| Package contents | 1 x DisplayPort cable |
| Package depth / length [mm] | 50 |
| Package height [mm] | 240 |
| Package width [mm] | 205 |
| Net weight [kg] | 0.290 |
| Gross weight [kg] | 0.296 |
| Warranty | 24 month |
| EAN code | 5901878527376 |