

Qoltec Fiber optic connector LC/APC | Singlemode | 3.0mm

Product code: 54162

Fiber optic connector for connecting optical fibers.
Connectors: LC/APC
Fiber type: Singlemode

CONFIDENCE CONFIRMED BY A WARRANTY

Do you want a high quality product? Our solutions will meet your expectations. Each connector we offer comes with a 24-month guarantee valid from the date of purchase.

TECHNICAL DATA

Producer	Qoltec
Type connectors	LC/APC
Fiber type	Singlemode
Usage	Indoor cable
Diameter cable	3.0 mm
Optical fiber diameter	125 m (657A, 657A2)
Tight buffer diameter	250 m
Working time	About 100s (no fiber cut)
Insertion loss	0.3 dB (1310nm, 1550nm)
Fastening strength of naked fiber	> 4 N
Fastening strength of naked fiber holder	> 8 N
Tensile strength	> 10 N
Drop-off test	IL 0.5 dB RL 5 dB
Operating temperature	-40 C ~ +75 C
On-line tensile strength (20N)	IL 0.5 dB RL 5 dB IL - insertion loss RL - return loss
Mechanical durability (500 times)	IL 0.5 dB RL 5 dB
Package	Polybag
Package depth / length [mm]	70
Package width [mm]	15
Package height [mm]	100
Net weight [kg]	0.0010
Gross weight [kg]	0.0020
Warranty	24 months
EAN code	5901878541624