

Qoltec Fiber optic connector SC/APC | Singlemode | 3.0mm

Product code: 54168

Fiber optic connector for connecting optical fibers.
Connectors: SC/APC
Fiber type: Singlemode

CONFIDENCE CONFIRMED BY A WARRANTY

Do you want a high quality product? Our solutions will meet your expectations. Each connector we offer comes with a 24-month guarantee valid from the date of purchase.

TECHNICAL DATA

Producer	Qoltec
Type connectors	SC/APC
Fiber type	Singlemode
Usage	Indoor cable. Drop cable.
Diameter cable	3.0 mm
Optical fiber diameter	125 m (657A, 657A2)
Tight buffer diameter	250 m
Working time	About 60s (no fiber cut)
Insertion loss	0.3 dB (1310nm, 1550nm)
Fastening strength of naked fiber	> 5 N
Fastening strength of naked fiber holder	> 10 N
Tensile strength	> 50 N
Drop-off test	IL 0.5 dB RL 5 dB
Operating temperature	-40 C ~ +75 C
On-line tensile strength (20N)	IL 0.5 dB RL 5 dB IL - insertion loss RL - return loss
Mechanical durability (500 times)	IL 0.5 dB RL 5 dB
Package	Polybag
Net weight [kg]	0.0030
Gross weight [kg]	0.0060
Warranty	24 months
EAN code	5901878541686