



Qoltec DIN rail power supply | 60W | 24V | 2.5A | Gray

Product code: 50921

DIN rail power supplies are industrial power supplies which, in addition to a sufficiently high degree of protection ensuring protection against external conditions, also have high power and efficiency parameters.

MULTI-SECTOR USE

DIN rail power supplies are a useful element of automation systems, machine control, lighting technology and industrial electronics where the size of the power supply devices and their adaptation to a limited space are important.

MATCH YOUR MODEL

Don't you know which power supply to choose? It's easy:

It is essential to calculate the power consumption of all devices it supports. The sum will allow to determine the minimum power that will ensure the operation of all components in the system powered by a specific DIN power supply. It is worth remembering that when choosing a power supply, provide a reserve of approx. 10-15% of power for the safe functioning of the equipment connected to it.

PRACTICAL SOLUTION

DIN rail power supplies are made of the highest quality materials to provide you with reliable power in any situation. Additionally, it has protection against:

- overvoltage protection against too low or too high input voltage,
- overloads are protection against overloads of each of the power lines,
- short circuits is a protection against short circuits in the power supply circuit,
- thermal is protection against overload or bad air circulation.

TRUST CONFIRMED BY WARRANTY

DIN rail power supplies are made of the highest quality materials to provide you with reliable power in any situation. Additionally, it has protection against:

- overvoltage protection against too low or too high input voltage,
- overloads are protection against overloads of each of the power lines,
- short circuits is a protection against short circuits in the power supply circuit,
- thermal is protection against overload or bad air circulation.

TECHNICAL DATA

Producer	Qoltec
Usable power	60 W
Input voltage	220 - 240 V
Output voltage	24 V
Range of output voltage regulation	23-25 V dc
Output current	2.5 A
Frequency	50 - 60 Hz
Efficiency	85%
Security	- overvoltage protection - overload protection - short-circuit protection
Additional information	For use only with a device conforming to the specifications indicated in the device's specification
Additional information	Mounting on DIN rail TS35 / 7.5 or 15 Output voltage adjustment
IP rating	IP 20
Working temperature	-20 C ~ +50
Colour	Grey
Dimensions (D/L x W x H)	53 x 58 x 92 mm
Package contents	DIN rail power supply
Package depth / length [mm]	102
Package width [mm]	60
Package height [mm]	69
Net weight [kg]	0.1830
Gross weight [kg]	0.2030
Certifications	CE
Warranty	24 months
EAN code	5901878509211