

Qoltec Displayport Alternate mode | USB 3.1 type C male | HDMI A male | 4K | 2m

Product code: 50415

The solutions used will allow you to enjoy the highest quality of image and sound:
- Resolution: max. 4K (30Hz)
- 8 audio channels
- 144Hz (1080p) refresh rate
- USB-C is rotationally symmetrical connector

Make sure that your devices support standard DisplayPort Alternate Mode USB-C 3.1 and standard HDMI type A.

4K PICTURE ON A LARGE SCREEN



USB-C to HDMI without additional adaptors

The Qoltec cable allows you to transmit video from a device equipped with a USB-C port directly to a monitor, TV or projector with an HDMI input. Support for DisplayPort Alternate Mode allows you to use the USB-C port to transmit audio-video signals at resolutions up to 4K.

SMOOTH AND FAST TRANSMISSION



Up to 10Gb/s and a refresh rate of up to 144Hz

A bandwidth of up to 10Gb/s ensures efficient signal transmission, whilst a maximum refresh rate of up to 144Hz delivers a smoother picture on compatible devices. The cable supports both RBR and HBR transmission modes, making it ideal for both work and multimedia use.

RICH COLOUR REPRODUCTION

RGB, Y CBCR and colour depth up to 48 bits/px

The cable supports the RGB, Y CBCR 4:4:4 and Y CBCR 4:2:2, as well as the ITU-R BT.601 and ITU-R BT.709 colour spaces. A maximum colour depth of up to 48 bits/px allows for the transmission of extensive colour information in compatible hardware configurations.

TRUST BACKED BY A GUARANTEE

This product comes with a 24-month warranty
Do you want to be sure of the high quality of the product you're buying? **Our solutions will meet your expectations.** Every cable we offer comes with a 24-month warranty, valid from the date of purchase.

TECHNICAL DATA

Producer	Qoltec
Type	USB-C 3.1 male / HDMI A male
Standard	DP 4K
Capacity	10.0Gb/s
Transmission mode	RBR, HBR
Resolution	max. 4K
Refresh rate	max. 144Hz
Colour Format	RGB, Y CBCR 4:4:4, Y CBCR 4:2:2
Depth of Colors	48bit/px
Colour Space	ITU-R BT.601, ITU-R BT.709
Maximum audio Channels	8
Application	tablet, smartphone, laptop, PC
Additional information	The connector supports Alternative DisplayPort mode Shielded
OTHER PARAMETERS	
Colour	White
Working temperature	-20 C ~ +60
Cable length	2m
Package	Polybag
Package depth / length [mm]	170
Package height [mm]	260
Package width [mm]	15
Net weight [kg]	0.0800
Gross weight [kg]	0.0900
EAN code	5901878504155