



## Qoltec DisplayPort v1.4 male | DisplayPort v1.4 male | 8K | 2m

Product code: 50587

The solutions used will allow you to enjoy the highest quality of image and sound:

- Resolution: max. 8K
- High Bit Rate 3 Technology
- 32 audio channels
- 240Hz (1440p) refresh rate
- Display Stream Compression 1.2 (DSC),
- Forward Error Correction (FEC),
- High Dynamic Range 10 (HDR10)
- Multi-Stream Transport (MST)
- Dual-mode for DVI and HDMI adapters

Make sure that your devices support standard DisplayPort v1.4

### CREATE UNFORGETTABLE EXPERIENCES WITH 8K IMAGING



DisplayPort 1.4 – 8K and HDR with 32.4 Gb/s Bandwidth

**DisplayPort 1.4 is the latest standard that takes image and sound quality to a whole new level!** With an exceptional bandwidth of **32.4 Gb/s** and support for **8K resolution at 60 Hz**, it offers unprecedented image clarity, ideal for professional use and top-quality entertainment. You gain the ability to work with multiple monitors simultaneously, and thanks to HDR technology, contrast and colors are even more intense, ensuring an unparalleled visual experience. **DisplayPort 1.4** is a great choice for those looking for a cable that meets the demands of both gaming and professional video and graphic design applications.

## DISPLAYPORT 1.4 – TAKE A STEP INTO THE FUTURE WITH THE HIGHEST QUALITY MULTIMEDIA

8K Video, 32-Channel Audio, and DSC Technology for Professional and Home Use

The DisplayPort 1.4 cable is the ideal solution for anyone seeking the highest visual and audio quality, whether for professional applications or home entertainment. Thanks to its advanced technology, you can enjoy **an exceptional multimedia experience** that will satisfy even the most demanding users.

- **Maximum resolution of 8K (30Hz)** – thanks to **High Bit Rate 3 (HBR3)** technology, you'll see every detail,
- **32 audio channels** – digital-quality surround sound that will transport you to a whole new dimension,
- **Maximum refresh rate of 240 Hz (144Op)** – smooth images and a more comfortable viewing experience,
- **Display Stream Compression 1.2 (DSC), Forward Error Correction (FEC), High Dynamic Range 10 (HDR10)** – thanks to this technology, the transmitted image is of the highest quality,
- **Multimedia connectivity** – connect devices such as a TV, computer, laptop, projector, home theater system, or audio equipment,
- **Multi-Stream technology** – the ability to connect multiple monitors using a single cable and an appropriate splitter,
- **Dual Mode for DVI and HDMI Adapters** – enables support for the **HDMI 2.0** standard and **HDCP 2.2** content protection, ensuring security and convenience.

## VERSATILITY THAT MAKES ALL THE DIFFERENCE – CHOOSE THE FUTURE OF VIDEO TECHNOLOGY

DisplayPort 1.4 – An Improvement Over Version 1.3 Thanks to HDR and Multi-Streaming

DisplayPort 1.4 is the next step in the evolution of this technology, offering **a bandwidth of 32.4 Gb/s**, which allows for support of **8K at 60 Hz** – but only for displays that support **Display Stream Compression (DSC)**. For displays without this technology, DisplayPort 1.4 offers the same limits as **DisplayPort 1.3**, namely resolutions up to **4K at 120 Hz**. Despite this, version 1.4 still provides better image quality thanks to support for **HDR**, enabling more accurate color reproduction and higher contrast.

Compared to version 1.3, DisplayPort 1.4 also adds support for **multi-streaming**, allowing you to connect multiple monitors using a single cable. It also offers greater flexibility in terms of resolution and refresh rate, making it more versatile and better suited for modern display technologies.

## DISPLAYPORT 1.4 CABLE WITH DSC – A BREAKTHROUGH IN PICTURE QUALITY THAT WILL TRANSPORT YOU TO A WHOLE NEW DIMENSION

DisplayPort 1.4: DSC (Display Stream Compression) – Smooth 8K Video

The DisplayPort 1.4 cable features advanced **Display Stream Compression 1.2 (DSC)** technology, which enables lossless image compression. Thanks to this technology, even at 8K resolution, users can enjoy exceptional visual quality without losing any detail. DSC provides higher bandwidth while maintaining the highest image quality, enabling smooth playback of even the most demanding content, such as 8K videos, games, or professional graphics applications. This solution is the key to achieving the best visual experience, regardless of usage intensity.

## THE FUTURE OF CONNECTIVITY: SECURITY, QUALITY AND CONVENIENCE ALL IN ONE !

DisplayPort 1.4 Cable – Shielded, Nickel-Plated Connectors, and Various Lengths

The DisplayPort 1.4 cable is an exceptionally durable and functional solution that ensures reliability in all conditions.

- Thanks to its **shielding, it effectively protects against electromagnetic interference**, which ensures signal stability and excellent picture and sound quality.
- **Nickel-plated connectors increase resistance to corrosion and mechanical damage**, ensuring a long-lasting, reliable connection.
- The cable is available in lengths **ranging from 0.5 m to 3 m**, allowing for flexible adaptation to various setups—whether in the office, a home theater, or when connecting a projector.

## TRUST BACKED BY A GUARANTEE

This product comes with a 2-year warranty

Do you care about the high quality of the product you're buying? **Our solutions are designed to meet your expectations.** Each of the DisplayPort cables we offer is covered by a 24-month warranty valid from the date of purchase.

## TECHNICAL DATA

|                             |                                                                                                                   |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------|
| Producer                    | Qoltec                                                                                                            |
| Type                        | DisplayPort male / DisplayPort male                                                                               |
| Standard                    | DP v1.4                                                                                                           |
| Capacity                    | 32.4 Gb/s                                                                                                         |
| Transmission mode           | RBR, HBR, HBR2, HBR3                                                                                              |
| Resolution                  | max. 8K                                                                                                           |
| Refresh rate                | max. 240 Hz                                                                                                       |
| Colour Format               | RGB, Y CbCr 4:4:4, Y CbCr 4:2:2, Y CbCr 4:2:0, 1.1 + Y-only (monochrome)                                          |
| Depth of Colors             | 48 bit/px                                                                                                         |
| Colour Space                | ITU-R BT.601, ITU-R BT.709, sRGB, scRGB, xvYCC, Adobe RGB (1998), DCI-P3, Simplified color profile, ITU-R BT.2020 |
| Maximum audio Channels      | 32                                                                                                                |
| Application                 | Laptop, PC                                                                                                        |
| Additional information      | Shielded                                                                                                          |
| OTHER PARAMETERS            |                                                                                                                   |
| Colour                      | Black                                                                                                             |
| Working temperature         | -20 C ~ +60                                                                                                       |
| Cable length                | 2 m                                                                                                               |
| Package                     | Polybag                                                                                                           |
| Package depth / length [mm] | 200                                                                                                               |
| Package height [mm]         | 260                                                                                                               |
| Package width [mm]          | 30                                                                                                                |
| Net weight [kg]             | 0.1200                                                                                                            |
| Gross weight [kg]           | 0.1350                                                                                                            |
| Warranty                    | 24 month                                                                                                          |
| EAN code                    | 5901878505879                                                                                                     |