



Qoltec Fiber optic connector LC/APC | Singlemode | 3.0mm

Product code: 54162

Fiber optic connector for connecting optical fibers.

Connectors: LC/APC

Fiber type: Singlemode

CONFIDENCE CONFIRMED BY A WARRANTY

Do you want a high quality product? Our solutions will meet your expectations. Each connector we offer comes with a 24-month guarantee valid from the date of purchase.

TECHNICAL DATA

Producer	Qoltec
Type connectors	LC/APC
Fiber type	Singlemode
Usage	Indoor cable
Diameter cable	3.0 mm
Optical fiber diameter	125 μm (657A, 657A2)
Tight buffer diameter	250 μm
Working time	About 100s (no fiber cut)
Insertion loss	0.3 dB (1310nm, 1550nm)
Fastening strength of naked fiber	> 4 N
Fastening strength of naked fiber holder	> 8 N
Tensile strength	> 10 N
Drop-off test	IL 0.5 dB RL 5 dB
Operating temperature	-40 °C ~ +75 °C
On-line tensile strength (20N)	IL 0.5 dB RL 5 dB IL - insertion loss RL - return loss
Mechanical durability (500 times)	IL 0.5 dB RL 5 dB
Package	Polybag
Package depth / length [mm]	70
Package width [mm]	15
Package height [mm]	100
Net weight [kg]	0.0010
Gross weight [kg]	0.0020
Warranty	24 months
EAN code	5901878541624