



## Qoltec Fiber optic connector SC/UPC | Multimode | 3.0mm

Product code: 54170

Fiber optic connector for connecting optical fibers.

Connectors: SC/UPC

Fiber type: Multimode

### CONFIDENCE CONFIRMED BY A WARRANTY

Do you want a high quality product? Our solutions will meet your expectations. Each connector we offer comes with a 24-month guarantee valid from the date of purchase.

## TECHNICAL DATA

|                                          |                                                                  |
|------------------------------------------|------------------------------------------------------------------|
| Producer                                 | Qoltec                                                           |
| Type connectors                          | SC/UPC                                                           |
| Fiber type                               | Multimode                                                        |
| Usage                                    | Indoor cable. Drop cable.                                        |
| Diameter cable                           | 3.0 mm                                                           |
| Optical fiber diameter                   | 125 m (657A, 657A2)                                              |
| Tight buffer diameter                    | 250 m                                                            |
| Working time                             | About 60s (no fiber cut)                                         |
| Insertion loss                           | 0.3 dB (1310nm, 1550nm)                                          |
| Fastening strength of naked fiber        | > 5 N                                                            |
| Fastening strength of naked fiber holder | > 10 N                                                           |
| Tensile strength                         | > 50 N                                                           |
| Drop-off test                            | IL 0.5 dB RL 5 dB                                                |
| Operating temperature                    | -40 C ~ +75 C                                                    |
| On-line tensile strength (20N)           | IL 0.5 dB RL 5 dB<br><br>IL - insertion loss<br>RL - return loss |
| Mechanical durability (500 times)        | IL 0.5 dB RL 5 dB                                                |
| Package                                  | Polybag                                                          |
| Package depth / length [mm]              | 70                                                               |
| Package width [mm]                       | 15                                                               |
| Package height [mm]                      | 100                                                              |
| Net weight [kg]                          | 0.0030                                                           |
| Gross weight [kg]                        | 0.0040                                                           |
| Warranty                                 | 24 months                                                        |
| EAN code                                 | 5901878541709                                                    |