

Qoltec Overvoltage power strip for RACK 19" with CB | 1U | 16A | PDU | 6xFRENCH | 2m

Product code: 53995

The PDU power strip is a product made of high-quality materials that guarantee safe access to energy. Perfect for RACK server cabinets. Our device offers:
- overvoltage protection,
- electric strength,
- grounding continuity,
- insulation strength,
- illuminated switch,
- circuit breaker
- 2m power cord.

POWER STRIP FOR SPECIAL TASKS

Do you run a company or operate a small server room at home? You are probably familiar with the topic of RACK cabinets. They are indispensable in companies that value reliability. Choosing the right equipment should always be carefully considered, but we often forget about the key issue, which is a reliable power supply. The Qoltec power strip for RACK cabinets will be perfect for this role.

COMFORT AND USING QUALITY

The choice of power strip becomes obvious when we take into account the functionality and quality of workmanship. It is worth remembering that the functionality, quality of materials from which it is, as well as find a place:
- purchase against surges - protects the equipment against voltage differences,
- illuminated equipment - gives the possibility of quick localization of the power source,
- circuit breaker - additionally increases safety connected devices
- 2m cable - thanks to it you can conveniently mount the strip in your RACK cabinet

WE MEET ALL REQUIREMENTS

Our surge protectors for RACK cabinets have CE and RoHS certificates.
They also passed tests on:
- electric strength (Hipo test),
- grounding continuity,
- insulation strength

CONFIDENCE CONFIRMED BY A WARRANTY

If you value the quality of purchased equipment our projects and solutions are focused on meeting your expectations. Qoltec overvoltage power strip for RACK cabinets are covered by 12 months warranty.

TECHNICAL DATA

Producer	Qoltec
Input voltage	220 - 250 V
Max. input current	16 A
Output voltage	250 V
Output frequency	50 - 60 Hz
Maximum load	3680 W
Input frequency range	50 - 60 Hz
Plug	DIN 49441, 16 A
Sockets	6 x FRENCH (NFC61-314)
Fire resistance rating	UL 94V-0
Working height	1U
Mounting method	Horizontal or vertical installation
Mounting length	465 mm
Cable length	2 m
Tests	Hi-pot test, grounding test, IR test
Protection	Overload
Usage	Power supply in RACK 19" cabinet
Additional information	Backlit switch Circuit breaker
OTHER PARAMETERS	
Colour	Black
Material	Aluminum
Dimensions	482.6 x 44.4 x 62 mm (19")
Package depth / length [mm]	90
Package width [mm]	60
Package height [mm]	510
Net weight [kg]	0.7370
Gross weight [kg]	0.8180
Certifications	CE, RoHS
Warranty	24 months
EAN code	5901878539959