



## Qoltec Patchcord fiber optic LC/UPC - LC/UPC | Multimode | 50/125 | OM2 | Duplex | 15m

Product code: 54028

---

Patchcord fiber optic multimode  
Connectors: LC/UPC - LC/UPC  
Standard: OM2  
Diameter cable: 3.0 mm  
Cable length: 15 m

### CONFIDENCE CONFIRMED BY A WARRANTY

Do you want a high quality product? Our solutions will meet your expectations. Our cables are covered for 24-month warranty from the date of purchase.

TECHNICAL DATA

|                                  |                                                                                                                                                                                                             |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Producer                         | Qoltec                                                                                                                                                                                                      |
| Type patchcord                   | Multimode                                                                                                                                                                                                   |
| Type connectors                  | LC/UPC - LC/UPC                                                                                                                                                                                             |
| Type of fiber optic transmission | Duplex                                                                                                                                                                                                      |
| Standard fiber                   | OM2                                                                                                                                                                                                         |
| Fiber type                       | 50/125                                                                                                                                                                                                      |
| Fiber core diameter              | 50 m                                                                                                                                                                                                        |
| Diameter fibers sheath           | 125 m                                                                                                                                                                                                       |
| Sheath                           | LSZH                                                                                                                                                                                                        |
| Diameter cable                   | 3.0 mm                                                                                                                                                                                                      |
| Insertion loss                   | <0.3 dB                                                                                                                                                                                                     |
| Return loss                      | 35 - 39 dB                                                                                                                                                                                                  |
| Reinforcing element              | Aramid fiber                                                                                                                                                                                                |
| Additional information           | Easy installation and handling on high speed fiber optical transmission networks.<br>LSZH - Outside fireproof cable sheath, which the fire does not emit harmful gases.<br>The product individually tested. |
| OTHER PARAMETERS                 |                                                                                                                                                                                                             |
| Colour                           | Orange                                                                                                                                                                                                      |
| Cable length                     | 15 m                                                                                                                                                                                                        |
| Package                          | Polybag                                                                                                                                                                                                     |
| Net weight [kg]                  | 0.2050                                                                                                                                                                                                      |
| Gross weight [kg]                | 0.2100                                                                                                                                                                                                      |
| Warranty                         | 24 months                                                                                                                                                                                                   |
| EAN code                         | 5901878540283                                                                                                                                                                                               |

|              | 100 Mb Ethernet | 1 Gb Ethernet | 10 Gb Ethernet | 40 Gb Ethernet | 100 Gb Ethernet |
|--------------|-----------------|---------------|----------------|----------------|-----------------|
| OM2 (50/125) | 2km             | 550m          | 82m            | Nie wspiera    | Nie wspiera     |
| OM3 (50/125) | 2km             | 800m          | 300m           | 100m           | 100m            |
| OM4 (50/125) | 2km             | 1100m         | 550m           | 125m           | 125m            |