



Qoltec Proximity card and key fob reader

Product code: 52446

Qoltec's proximity card and key fob reader operates at a frequency of 125kHz. The device secures and allows identification of users and full control of access to selected objects. The reader can be unlocked with a card or key fob. It has a built-in LED diode and buzzer.

HOW DOES THE ACCESS CONTROL SYSTEM WORK ?

An access control system is a convenient tool for controlling the flow of people who are in a security area. It is a widely used security not only in large corporations, offices, archives, server rooms or industrial plants. It is a system with which we also come into contact on a daily basis in public facilities such as swimming pools, gyms, parking lots and libraries.

AUTOMATE YOUR FACILITY

The proximity reader helps identify individual users. Each person is verified by the access control reader with an identifier in the form of a proximity card or key fob before gaining access to a security area. The use of a proximity reader restricts access to buildings or rooms only to authorized persons.

TAKE CARE OF SECURITY

The Qoltec brand proximity reader allows you to program up to **2000 users**. The device has a built-in LED diode and a sound signal. The correct operation after reading the card is indicated by the green color of the LED and one sound signal. After 10 unsuccessful access attempts in one minute, the lock will activate and the reader will be automatically locked for a period of 10 minutes.

ELEGANT AND SOLID CONSTRUCTION WITH ATTENTION TO EVERY DETAIL

We make sure that the products of our brand are united not only by the aesthetics of workmanship, but also by durability. Solid workmanship guarantees the durability of the product and is a guarantee of use for many years.

CONFIDENCE CONFIRMED BY A WARRANTY

Do you care about the high quality of the product you buy? Our solutions will meet your expectations. Product is covered by a 24-month warranty valid from the date of purchase.

TECHNICAL DATA

Producer	Qoltec
Type	EM
Type of transmission	RFID
Operating mode	Code/card/proximity tag
Nominal voltage	DC10 -12V
Frequency	125 kHz
Load capacity	<100mA
Max number of users	2000
Number of relay outputs	1
Touch keyboard	No
Proximity reader	Yes
Opened via smartfone	No
Installation	Surface mouting
IP Rating	IP68
Additional information	It has a built-in LED diode and buzzer.
OTHER PARAMETERS	
Working temperature	-40 +60
Dimensions (D/L x W x H)	35 x 42 x 100 mm
Package depth / length [mm]	70
Package width [mm]	112
Package height [mm]	75
Net weight [kg]	0.219
Gross weight [kg]	0.288
Warranty	24 month
EAN code	5901878524467