



Qoltec Uninterruptible Power Supply UPS RACK | 6KVA | 4800W | LCD

Product code: 53943

RACK UPS adapted for mounting in rack cabinets. It's perfect for anyone who wants to have control over the stable operation of their devices regardless of fluctuations in the power supply. In order to provide emergency power backup, an additional battery module is required (53944)

DISCOVER SAFE ENERGY

Do you have a small server room, or maybe you run a company? Do you store private data on the server, or is it filled with important information? We know how important safety and maintenance of constant energy access to your devices are for you. Don't let voltage outages and decreases affect your work. The RACK UPS is a solution that provides a constant supply of energy which is necessary for the stable operation of your devices.

APPEARANCE AND FUNCTIONALITY

The built-in LCD display guarantees easy management of the device operation. Thanks to this, you regularly receive information about the status of work and parameters, making work easy, fast and reliable.

BETTER QUALITY WORK

- Pure sine wave - security basis and guarantee of compatibility with any type of power supply,
- Overload protection, short circuit protection and high-temperature protection,
- Double conversion - guarantee that a stable power supply with constant parameters is supplied to your devices,
- Ability to mount an SNMP card or connect an SNMP adapter - it is a network management standard that allows you to collect information about connected devices or configure their parameters quickly and easily,
- USB port - thanks to the UPS management software, you can monitor its operation on an ongoing basis and adapt it to your needs,
- RJ-45 port - provides security against overvoltage via LAN.

CONFIDENCE CONFIRMED BY A WARRANTY

You value the quality of purchased equipment so our projects and solutions are focused on meeting your expectations. RACK UPS is covered by 24 months warranty.

TECHNICAL DATA

Producer	Qoltec
Wave form	Pure sine wave
Transfer time	4 ms
Range voltage	Input voltage: 230 Vac (50 Hz - 60 Hz) Output voltage: 220 Vac ~ 230 Vac 10% (50 Hz - 60 Hz)
Built-in battery	No
Rated capacity	6 KVA
Usable power	4800 W
Power factor	0.8
Output sockets	1 x RJ45 1 x USB type B
Power factory	0.8
Load type	Devices sensitive to the occurrence of voltage jumps, PC
Noise	50 dB
Safety	Overload protection Overvoltage protection Short circuit protection High and low voltage protection
Operating temperature	20°C ~ +40°C
Additional information	Height lower than 1000m.: without derating Height above 1000m n.m.p.: 1% reduction of the rated parameters for every 100m of growth The ability to mount an SNMP card or connect an SNMP adapter
Package contents	User manual Warranty card CD with software
Housing color	Black
Usage	Data processing centers Industrial and production environments Medical centers Application in places where operational reliability is required
Dimensions	660 x 430 x 130 mm 3U
Net weight [kg]	15.9000
Gross weight [kg]	20.0000
Warranty	24 months
EAN code	5901878539430